

HIGH FLOW CHLORAMINE REDUCTION WATER FILTER SYSTEM



WaterMark Certified AS/NZS 3497

- Compact 14" Design for Undersink Installation
- Suitable for Mains Water or Tank Water
- Quick Change Cartridge Easy Maintenance
- For use with existing taps or appliances
- High Flow Rate Up to 8L/Min
- Reduces Pesticides & other hazardous chemicals
- Inhibit Limescale to protect pipes & fixtures
- Removes Chloramine & Chlorine

HIGH FLOW CHLORAMINE FILTER SYSTEM

The HPF[®] EPA Quick Change Cartridge provides your family with clean, fresh great tasting water suitable for use in a wide range of applications.

HIGHLIGHTS

Simple and effective water filtration with their combination of high-performance carbon, unique binders and proprietary manufacturing processes, these systems deliver minimal drop in water pressure, High dirt holding capacity and excellent contaminant reduction.

With a rating of 5uM for particulate filtration, this filter reduces Chloramines, Sediment and Chemical with exceptional flow rate capabilities.

The CRC 14" quick change cartridge is a unique cartridge which has been specifically designed for chloramine reduction and has been tested by the manufacturer in accordance followed by NSF/ANSI standard and is Compliant with NSF/ANSI protocol. The CRC 14" cartridge combines 3 main principles of filtration into 1 single Filter cartridge including Chloramine Reduction, Particulate Filtration down to 5uM by mechanical means & Chlorine, Pesticides, Hazardous Chemicals, Tastes and Odour reduction.

SPECIFICATIONS

Operating Pressure	10 psi (69 kPa) - 125 psi (860 kPa)
Operating Temperature	4°C - 55°C
Tested Flow Rate	4L/Min for >85% Reduction
Maximum Flow Rate*	Up to 8L/Min
Service Life (Litres)	19,000L > 85% Reduction
Service Life (Time)	12 Months
Initial Lead Reduction Rate	>99%
Head Cap Ports	3/8" Female
Compatibility (Head Cap)	Everpure, Pentair, WFA HiFlow (Pre-2017)
Superior Replacement For	Everpure EV977100 7CLM+

